



EC Declaration of Conformity
(Construction Products Directive)

Address of Manufacturer:

Knauf Insulation Ltd.,
Chemistry Lane,
Pentre,
Queensferry,
Flintshire
CH5 2DA
U.K.

Notified Certification Body :

BSI Product Services
(Appr. Body ID 0086)
Maylands Ave.,
Hemel Hempstead,
Herts.,
HP2 4SQ
U.K.

Product Description & Use :

Factory made mineral wool thermal insulation in the form of rolls, batts, boards, and slabs for use in thermal insulation of buildings.

See attachment for product/trade names and declared values.

Particular provisions for the end use of the product :

None

Conforms to the Provisions of :

Construction Products Directive
EN13162:2001 Thermal insulation products for buildings – Factory made mineral wool (MW)
products manufactured with phenol formaldehyde or ECOSE™ Technology binder systems.

Certificate of Conformity No. : 0086-CPD-466628

Signed on behalf of manufacturer



Name: Kevin Day

Position: Plant Manager

Date: 10/06/2009



EC Samsvarserklæring (Direktiv for byggevarer)

Produsentens adresse: Knauf Insulation Ltd., Chemistry Lane Pentre Queensferry Flintshure CH5 2DA STORBRITANNIA	Teknisk kontrollorgan BSI Product Services (ID-nr. 0086) Maylands Ave., Hemel Hempstead Herts HP2 4SQ STORBRITANNIA
---	---

Produktbeskrivelse og bruk:

Fabrikkprodusert, termisk isolasjon av mineralull i form av ruller, blokker og plater som brukes til termisk isolering av bygninger.

Se vedlegg for produkt-/varebetegnelse og angitte verdier.

Spesielle forskrifter for sluttbruk av produktet:

Ingen

Samsvarer med forskriftene i:

Direktiv for byggevarer

EN 13162:2001 Termiske isolasjonsprodukter for bygninger - produkter av fabrikkprodusert mineralull (MW) - laget av bindemidler basert på formaldehyd eller naturlige bindemidler basert på ECOSE-teknologi

Samsvarssertifikat nr.:

0086-CPD-466628

Signert på vegne av produsent:

Navn: Kevin Day

Stilling: Fabrikk sjef

Dato: 10/06/2009

Declaration of Conformity

Product Name / Trade Name	Thickness Range (mm)	Reaction to Fire Class (Euroclass)	Thermal Conductivity (W/mK)	Designation Code
Rocksilk® Universal Slab				
Universal Slab RS33	30 - < 50	A1	0.037	MW-EN13162 - T2
Universal Slab RS33	50 - 200	A1	0.037	MW-EN13162 - T4
Universal Slab RS45 to RS150	25 - < 50	A1	0.035	MW-EN13162 - T2
Universal Slab RS45 to RS150	50 - 200	A1	0.035	MW-EN13162 - T4
Universal Slab RS160 & RS170	25 - < 50	A1	0.037	MW-EN13162 - T2
Universal Slab RS180 & RS200	25 - 50	A1	0.036	MW-EN13162 - T4
Universal Slab RS160 & RS170	50 - 100	A1	0.037	MW-EN13162 - T4
Rocksilk® Universal Slab Water Repellent				
Universal Slab RS33WR	30 - < 50	A1	0.037	MW-EN13162 - WS - T2
Universal Slab RS33WR	50 - 200	A1	0.037	MW-EN13162 - WS - T4
Universal Slab RS45WR to RS150WR	25 - < 50	A1	0.035	MW-EN13162 - WS - T2
Universal Slab RS45WR to RS150WR	50 - 200	A1	0.035	MW-EN13162 - WS - T4
Rocksilk® Dritherm Cavity Slab				
Dritherm Cavity Slab	30 - < 50	A1	0.037	MW-EN13162 - WS - T2
Dritherm Cavity Slab	50 - 200	A1	0.037	MW-EN13162 - WS - T4
Rocksilk® Flexible Slab				
Flexible Slab	30 - < 50	A1	0.037	MW-EN13162 - T2
Flexible Slab	50 - 200	A1	0.037	MW-EN13162 - T4
Rocksilk® Universal Slabs – Foil Faced				
Universal Slab RS45 FF to RS140FF	25 - < 50	A1	0.035	MW-EN13162 - T2
Universal Slab RS45FF to RS140FF	50 - 100	A1	0.035	MW-EN13162 - T2

Declaration of Conformity

Product Name / Trade Name	Thickness Range (mm)	Reaction to Fire Class (Euroclass)	Thermal Conductivity (W/mK)	Designation Code
Rocksilk® Roof Slabs				
Krimpact™ Flat Roof Slab	50-150	A1	0.038	MW-EN13162-T5-WS
Krimpact™ Flat Roof Slab Extra	50-110	A1	0.039	MW-EN13162-T5-WS
Krimpact™ Flat Roof Light	25 - <50	A1	0.038	MW-EN13162-T2-WS
Krimpact™ Flat Roof Light	50-100	A1	0.038	MW-EN13162-T4-WS
Pitched Roof Slab	25-100	A1	0.038	MW-EN13162-T5-WS
Rocksilk Roofboard 100	25-<50	A1	0.038	MW-EN13162-T2-WS
Rocksilk Roofboard 100	50-100	A1	0.038	MW-EN13162-T4-WS
Rocksilk Roofboard 150	50-100	A1	0.039	MW-EN13162-T5-WS
Knauf Flame Barrier Slab 140 CR100 to CR 159	50-150	A1	0.038	MW-EN13162-T4
Knauf Flame Barrier Slab 160 CR160 to CR180	50-100	A1	0.039	MW-EN13162-T4
Universal Slab CR100WR to CR159WR	40 - <50	A1	0.038	MW-EN13162-T2-WS
Universal Slab CR100 WR to CR159WR	50-150	A1	0.038	MW-EN13162-T4-WS
Rocksilk® Floor Slab				
Thermal Floorslab	25 - 100	A1	0.035	MW-EN13162-T6- CS(10)10-CP5
Thermal Floor Slab Plus	<50	A1	0.038	MW-EN13162-T2 - WS
Thermal Floor Slab Plus	50-100	A1	0.038	MW-EN13162-T4 - WS
Rocksilk® Façade Slab				
Krimpact Façade Slab	25-<50	A1	0.038	MW-EN13162 - T2 - WS
Krimpact Façade Slab	50-100	A1	0.038	MW-EN13162 - T4 - WS

Declaration of Conformity – Products for Nordic Region

Product Name / Trade Name	Thickness Range (mm)	Reaction to Fire Class (Euroclass)	Thermal Conductivity (W/mK)	Designation Code
EcoBatt Roofmax Products				
EcoBatt Roofmax 30	50 - 180	A1	0.037	MW-EN13162-T5-WS
EcoBatt Roofmax 40	50 - 180	A1	0.037	MW-EN13162-T5-WS
EcoBatt Roofmax 50	50 - 180	A1	0.038	MW-EN13162-T5-WS
EcoBatt Roofmax Ext	20 - 30	A1	0.035	MW-EN13162-T5-WS
EcoBatt Roofmax Ext CR	50 - 80	A1	0.038	MW-EN13162-T5-WS